


PRO*FROST -60° C



Elcold's PRO series is available in five sizes 130L, 230L, 300L, 360L, 485L net volume. Standard setting is -60° C air temperature in the freezer at an ambient temperature up to +30° C.



- Digital temperature display (0,1 digits)
- Controller protected by PP heavy duty cover
- High and low temperature alarm separately adjustable
- Alarm resets automatically when the temperature is normalized
- Interior made from strong white coated steel
- Strong castors with brakes
- A new generation of single compressor freezers, with purely environmental friendly gases
- Maintenance free system
- Low energy consumption
- Pure environmental friendly HC refrigerant
- 100 mm high performance CFC free foam insulation



Technical specifications :

| | | 11 XLT/ PRO 11 | 21 XLT/ PRO 21 | 31 XLT/ PRO 31 | 41 XLT/ PRO 41 | 60 XLT/ PRO 60 |
|-------------------------------|---------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Ambient temperature | °C | +10° to +30° | +10° to +30° | +10° to +30° | +10° to +30° | +10° to +30° |
| Net volume | litres | 130 | 230 | 300 | 360 | 485 |
| Net volume | cu. ft. | 4,6 | 8,1 | 10,6 | 12,8 | 17,3 |
| Height with 50 mm castors | mm | 920 | 920 | 920 | 920 | 920 |
| Height with open lid | mm | 1620 | 1620 | 1620 | 1620 | 1620 |
| Width | mm | 725 | 1055 | 1305 | 1505 | 1705 |
| Insulation thickness | mm | 100 | 100 | 100 | 100 | 80 |
| Depth incl. handle and hinges | mm | 730 | 730 | 730 | 730 | 730 |
| Power consumption at +25° C | Watts | 330 | 410 | 560 | 610 | 610 |
| Fuse | A | 10 | 10 | 10 | 10 | 10 |
| Temperature range | °C | -30° to -60° | -30° to -60° | -30° to -60° | -30° to -60° | -30° to -60° |
| Noise level | dBa | < 51 | < 51 | < 51 | < 51 | < 51 |
| Weight | kg | 53 | 68 | 78 | 89 | 95 |

MEDIEHUSET WIEGAARDEN 58 107252



Elcold Fryser Hobro ApS

Løgstørvej 81 Hørby · DK-9500 Hobro · Denmark

Phone +45 96 57 22 22 · Fax +45 98 52 46 85

E-mail: elcold@elcold.com · www.elcold.com